

杆塔材料汇总表							
杆塔 编号	塔型(呼高)	接腿配置		身段重量 (kg)	接腿重 量	塔脚坂重 量	单基塔重 (kg)
		塔腿	身段+接腿(m)				
1#	SJD34(30.0)	1	22.5+7.5	16399.7	816.0	237.1	19871.6
		2	22.5+7.5		816.0	237.1	
		3	22.5+4.5		511.5	237.1	
		4	22.5+3.0		380.1	237.1	
2#	SJD34(30.0)	1	22.5+7.5	16399.7	816.0	237.1	20019.1
		2	22.5+6.0		659.0	237.1	
		3	22.5+3.0		380.1	237.1	
		4	22.5+7.5		816.0	237.1	
3#	35B31-J3(29.0)	1	24.0+4.0	8201.0	316.5	144.5	10047.4
		2	24.0+5.0		400.1	144.5	
		3	24.0+4.0		316.5	144.5	
		4	24.0+3.0		235.3	144.5	
4#	35B31-Z2(42.0)	1	36.5+5.5	7374.7	280.6	44.0	8333.5
		2	36.5+4.5		224.8	44.0	
		3	36.5+2.5		138.7	44.0	
		4	36.5+2.5		138.7	44.0	
5#	35B31-Z2(26.0)	1	22.0+4.0	4551.8	161.3	41.2	5222.8
		2	22.0+4.0		161.3	41.2	
		3	22.0+2.0		91.8	41.2	
		4	22.0+2.0		91.8	41.2	
6#	35B31-J1(30.0)	1	24.5+5.5	6285.2	318.1	85.4	7573.4
		2	24.5+5.5		318.1	85.4	
		3	24.5+2.5		155.2	85.4	
		4	24.5+2.5		155.2	85.4	
7#	35B31-Z2(36.0)	1	31.0+5.0	6319.2	247.6	44.0	7222.8
		2	31.0+5.0		247.6	44.0	
		3	31.0+2.0		116.2	44.0	
		4	31.0+2.0		116.2	44.0	
8#	35B31-J2(24.0)	1	19.5+4.5	5817.2	255.1	100.4	7101.5
		2	19.5+4.5		255.1	100.4	
		3	19.5+3.5		217.4	100.4	
		4	19.5+2.5		155.1	100.4	
9#	35B31-J3(20.0)	1	17.0+2.0	6340.8	148.1	135.7	7540.3
		2	17.0+3.0		212.4	135.7	
		3	17.0+2.0		148.1	135.7	
		4	17.0+2.0		148.1	135.7	
10#	35B29-Z2(42.0)	1	37.0+2.0	6902.0	108.6	32.3	7720.2
		2	37.0+2.0		108.6	32.3	
		3	37.0+5.0		235.9	32.3	
		4	37.0+5.0		235.9	32.3	
11#	35B29-J3(30.0)	1	24.5+3.5	7240.5	225.3	103.3	8636.5
		2	24.5+2.5		158.4	103.3	
		3	24.5+4.5		268.4	103.3	
		4	24.5+5.5		330.7	103.3	
12#	35B29-Z2(33.0)	1	28.0+2.0	4786.4	86.8	32.6	5477.8
		2	28.0+2.0		86.8	32.6	
		3	28.0+5.0		193.7	32.6	
		4	28.0+5.0		193.7	32.6	
13#	35B29-Z2(27.0)	1	23.0+4.0	4101.6	133.7	28.5	4710.4
		2	23.0+4.0		133.7	28.5	
		3	23.0+3.0		113.7	28.5	
		4	23.0+3.0		113.7	28.5	
14#	35B29-Z2(30.0)	1	26.0+4.0	4549.3	141.7	32.2	5165.1
		2	26.0+4.0		141.7	32.2	
		3	26.0+3.0		121.3	32.2	
		4	26.0+2.0		82.3	32.2	
15#	35B29-J1(29.0)	1	25.5+2.5	5419.6	127.3	62.3	6230.4
		2	25.5+2.5		127.3	62.3	
		3	25.5+3.5		179.7	62.3	
		4	25.5+2.5		127.3	62.3	
16#	35B29-J4(12.0)	1	9.0+3.0	4298.1	155.4	109.6	5308.2
		2	9.0+3.0		155.4	109.6	
		3	9.0+3.0		155.4	109.6	
		4	9.0+2.0		105.5	109.6	

A1#	35B31-J4(18.0)	1	14.0+4.0	6601.4	300.1	178.0	8513.8
		2	14.0+4.0		300.1	178.0	
		3	14.0+4.0		300.1	178.0	
		4	14.0+4.0		300.1	178.0	
A2#	35B31-Z2(24.0)	1	20.0+4.0	4276.4	148.0	41.2	4944.3
		2	20.0+4.0		148.0	41.2	
		3	20.0+3.0		125.1	41.2	
		4	20.0+2.0		82.0	41.2	
A3#	35B31-Z3(23.0)	1	20.0+3.0	4885.8	136.8	42.3	5560.8
		2	20.0+2.0		95.4	42.3	
		3	20.0+3.0		136.8	42.3	
		4	20.0+3.0		136.8	42.3	
A4#	35B31-J1(20.0)	1	17.0+2.0	4572.9	113.5	85.4	5472.5
		2	17.0+3.0		165.5	85.4	
		3	17.0+2.0		113.5	85.4	
		4	17.0+3.0		165.5	85.4	
A5#	35B31-J1(25.0)	1	22.5+2.5	5721.3	152.3	85.4	6672.1
		2	22.5+2.5		152.3	85.4	
		3	22.5+2.5		152.3	85.4	
		4	22.5+2.5		152.3	85.4	
B1#	35B31-J4(24.0)	1	19.5+3.5	8463.8	306.8	186.9	10418.1
		2	19.5+4.5		370.6	186.9	
		3	19.5+3.5		306.8	186.9	
		4	19.5+2.5		222.5	186.9	
B2#	35B31-Z1(27.0)	1	22.0+4.0	4067.7	141.6	29.7	4834.9
		2	22.0+5.0		182.6	29.7	
		3	22.0+5.0		182.6	29.7	
		4	22.0+4.0		141.6	29.7	
B3#	35B31-Z2(36.0)	1	31.0+5.0	6319.2	247.6	44.0	7325.0
		2	31.0+5.0		247.6	44.0	
		3	31.0+3.0		167.3	44.0	
		4	31.0+3.0		167.3	44.0	
B4#	35B31-Z1(27.0)	1	22.0+4.0	4067.7	141.6	29.7	4674.9
		2	22.0+5.0		182.6	29.7	
		3	22.0+2.0		82.1	29.7	
		4	22.0+2.0		82.1	29.7	
C1#	35B31-J4(21.0)	1	17.0+3.0	7715.8	272.5	186.9	9667.0
		2	17.0+4.0		329.3	186.9	
		3	17.0+4.0		329.3	186.9	
		4	17.0+3.0		272.5	186.9	
C2#	35B31-Z2(26.0)	1	22.0+4.0	4551.8	161.3	41.2	5335.7
		2	22.0+4.0		161.3	41.2	
		3	22.0+4.0		161.3	41.2	
		4	22.0+3.0		135.2	41.2	
C3#	35B31-J3(27.0)	1	21.5+3.5	7437.2	269.5	144.5	9209.9
		2	21.5+5.5		403.6	144.5	
		3	21.5+4.5		324.3	144.5	
		4	21.5+2.5		197.3	144.5	
C4#	35B31-J2(23.0)	1	19.5+3.5	5817.2	217.4	100.4	7088.4
		2	19.5+3.5		217.4	100.4	
		3	19.5+3.5		217.4	100.4	
		4	19.5+3.5		217.4	100.4	
C5#	35B31-J1(20.0)	1	17.0+2.0	4572.9	113.5	85.4	5472.5
		2	17.0+3.0		165.5	85.4	
		3	17.0+3.0		165.5	85.4	
		4	17.0+2.0		113.5	85.4	
防盗螺栓增重(t)							6.941
合计(t)							238.31

丽水市正阳电力设计院				中电工程浙江青田东源镇、万山乡35MWp 复合利用光伏发电项目35千伏站内线路工程			施工图设计阶段
批准		校核		杆塔材料汇总表			
审核		设计					
项目负责人		日期	2020.09	图号	334-3B[S]200150I[S]-01-A0101-04	版本号	0